

ACT-3000

ACT-3000 is built with a stainless steel chassis with all controls easily accessible on the unit's back side. The ozone generator has built-in monitoring of all vital parameters and shuts down the unit in case of any errors. The unit can also be controlled via the built-in 4-20 mA interface.



TECHNICAL SPECIFICATION

Ozone production	
Concentration, max	80 ppm
Production	0 – 350 mg/h
Feed gas (Air)	
Quality	Indoor air (21% O ₂)
Filter class	F-7
Fan capacity, max	47 m ³ /h
Ambient conditions	
Temperature	0 to +40 °C (+32 to +104 °F)
Humidity, max	85 % (R. H.) Non-condensing
Electrical connections	
Voltage rating	230 VAC, 50 Hz
optional	115 VAC, 60 Hz
Power consumption, max	18 W
Dimensions	
Size (H x W x D)	225 x 100 x 80 mm (8.9 x 3.9 x 3.1 in)
Weight	2 kg (4.4 lbs)
IP class	20
Options	Stainless steel lockable wall-mount bracket

ADVANTAGES

- ✓ Stainless steel cabinet
- ✓ Very low noise level
- ✓ Adjustable ozone production (0-100%)
- ✓ Compact design
- ✓ Easy to maintain
- ✓ Built-in digital input
- ✓ Built-in 4-20 mA interface

